

INDUSTRIAL HEAVY DUTY TIMBER POLE LADDERS

TRADITIONAL MATERIALS STILL GIVING THE BEST PERFORMANCE...

- + Speciality product for use in Scaffolding only. Ladder must be tied off as per Work at Height regulations. EsSGee Ladder Clamp available on request.
- + Ideal for **TuFF** industrial environments, meets strength requirements of BS2037 Class 1
- + Rated to a maximum load and duty rating of 150kgs.

SUSTAINABLY SOURCED SCANDINAVIAN SPRUCE & EASTERN EUROPEAN BIRCH...

- + Hardwood rungs, tested to over 300kgs for maximum robustness.

BRITISH DESIGN FOR MAXIMUM SAFETY, COMFORT & DURABILITY...


- + Handmade using the same traditional methods used by **LFI** for over 70 years
- + Steel tie-roads under each rung make a rigid and durable structure
- + 10 Year Manufacturer's Warranty.

AVAILABLE
UP TO
5.5m



**WHY LFI?
MY WORK.
MY SAFETY.
MY LADDER.**

TIMBER POLE LADDER



Product SKU	Treads /Rungs	A Max Working Height**	B Length	C Max Standing Height*	Weight (Kg)
A7PT30	11	3.5	3.0	1.9	8.0
A7PT40	15	4.5	4.0	2.9	12.0
A7PT50	19	5.4	5.0	3.8	16.0
A7PT55	21	5.9	5.5	4.2	18.0

*Max Standing height is on the 4th rung down.
 **Max Working height is calculated as Max Standing height + 1.6m


OTHER DIMENSIONS

D Bottom Width	F Bottom Horn	G Rung Pitch	H Top Horn
0.36	0.23	0.25	0.14

**EsSGee
LADDER CLAMP**

**UNIVERSAL CLAMP TO SECURE A
TuFF POLE TO SCAFFOLD STRUCTURES**

- + Easy to fit
- + Fits all ladder types
- + Order part **M6LC01** with your **TuFF Pole** ladder



All dimensions in metre. All measurements are nominal.

Have an enquiry?

Call us on 01531 820541 or email info@lfi-ladders.co.uk

britishladders.co.uk

