



EN131-PROFESSIONAL PLATFORM STEP LADDERS WITH HANDRAILS

MANUFACTURED TO THE LATEST SAFETY STANDARD...

- + Certified to EN131-Professional
- + Tested to a gruelling 50,000 cycle "climbing" durability test
- + Rated to a maximum load and duty rating of 150kgs.

HEAVY-DUTY, HARD-WEARING HIGH-QUALITY BUILD...

- Deep 80mm serrated non-slip treads with ridge reinforcement & double riveting at each corner for maximum durability and comfort when working at height
- Large ribbed channel section stiles, box section back legs, steel hinge & reinforced bottom tread & horns for improved resistance to heavy usage
- + Heavy duty 3mm thick, 5 Bar chequer plate high grip platform.

DEPENDABLE, COMFORT & STABILITY...

- + Hard wearing, non-slip feet for maximum grip on all floor surfaces
- Equipped with tool tray for convenient storage
- Available with single or double sided handrails
- + 10 Year Manufacturer's Warranty
- + Sizes available: 3 to 10 treads (including platform),.

















PLATFORM STEPLADDERS

Product SKU	No. of Treads***	Max Working Height**	B x F Length x Width	C Max Standing Height*	G Open Depth	Weight (kg)
K3PF03HR	3	2.2	1.37 x 0.46	0.6	0.74	6.5
K3PF04HR	4	2.5	1.60 x 0.49	0.9	0.93	7.3
K3PF05HR	5	2.7	1.84 x 0.52	1,1	1.12	8.2
K3PF06HR	6	2.9	2.09 x 0.55	1.3	1.31	9.1
K3PF07HR	7	3.2	2.33 x 0.59	1.6	1.50	10.0
K3PF08HR	8	3.4	2.58 x 0.62	1.8	1.69	10.9
K3PF09HR	9	3.6	2.82 x 0.66	2.0	1.88	11.8
K3PF10HR	10	3.8	3.07 x 0.69	2.2	2.07	12.7

*Max Standing Height is on the platform

**Max Working Height is calculated as Max Standing Height + 1.6m

***Number of treads includes the platform

Side View Closed	Side View Open	Front View
Closed Depth		Top Width Max Working Height Tread Pitch

COMMON DIMENSIONS

D		н	J	K
Tread Pitch	Top Width	Bottom Horn	Top Width	Closed Depth
0.26	0.33	0.16	0.28	0.13*

*Closed depth with handrails is 0.23

All dimensions in metre. All measurements are nominal.













